

## SUPRA TRICO 1RCA-1BNC DIGITAL

Digital SDI S/PDIF 75 Ohm Gauge: Triax 0.71mm<sup>2</sup> / AWG 19 Rev.date: 2023-08-10 Customs tariff no: 8544499390 Country of origin: Sweden

- True 75 ohm Matches 75 ohm transmissions without losses
- Exceptionally low damping factor allows for long cable runs
- PE foam insulation, extremely low capacitance
- Silver plated OFC wires exceptional high frequency conductivity

Trico 1RCA-1BNC digital Digital interconnet SDI & S/PDIF 75 Ohm

The Supra Trico true 75 Ohm digital interconnects are designed for numerous digital & video transmissions that require a closely matched characteristic impedance with exceptional bandwidth, e.g. between computer and DAC and video transmissions. Trico have the required high bandwidth to transfer the full digital spectrum with a well controlled signal integrity, display sufficient head room to max performance even for longer transmissions and extremely low capacitance, the most benign characteristic there is for transfering digital square waves.

Supra Trico-RCA/BNC is a single-end interconnect, suitable for e.g. SDI, CD drive to DAC or AV amplifier.

## CONSTRUCTION

| Cable:  | SUPRA Trico   |     |            |               |     |        |
|---|---|-----|------------|---------------|-----|--------|
| Jacket:   | PVC GA78, round   |     |            |               |     |        |
| Diameter:   | 8.3mm   |     |            |               |     |        |
| Colour:   | Iceblue (other colour upon order)                                   |     |            |               |     |        |
| Marking:  | SUPRA Trico > Made in Sweden > Meter mark                           |     |            |               |     |        |
| Screen connection:  | Semi-balanced, the outer screen is only connected at the source end |     |            |               |     |        |
| Connectors:   | SUPRA PPX RCA & Neutrik BNC NBLC75BSX14                             |     |            |               |     |        |
| - Type:   | 1 RCA male > 1 BNC male   |     |            |               |     |        |
| - Material:   | Pins of 24K Gold plated OFC   |     |            |               |     |        |
| - Colour:   | Anthracite grey & Silver/black                                      |     |            |               |     |        |
| - Locking:  | Expansion clamping to the chassis female RCA & Twist-lock           |     |            |               |     |        |
| Solder tin:   | Almit SR34 Super  |     |            |               |     |        |
| Signal direction:   | Follow the arrows > Source > Receiver                               |     |            |               |     |        |
| Packing <4m:  | Blister 25 x 21.5 x 4.8cm   |     |            |               |     |        |
| Packing >4m:  | Blister 31.5 x 25.4 x 6cm   |     |            |               |     |        |
| Special length are made upon order, add only additional cost per extra meter. |   |     |            |               |     |        |
|   | 1   |     | 7          | 1             |     |        |
| PRODUCT   |   | Qty | Part.no    | EAN-13        | Crt | Weight |
| TRICO 1RCA-1BNC   | DIGITAL 1M  | 1PC | 1001901527 | 7330060063466 | 25  | 0,30   |
|   |   |     |            |               |     |        |
| TRICO 1RCA-1BNC DIGITAL 2-100m are made upon order                            |   |     |            |               |     |        |
|   |   |     |            |               |     |        |



www.supracables.se