


SUPRA 4BNC-4BNC AUDIO/VIDEO

Audio/Video Multi Core Co-ax 75 Ohm

Gauge: 4x1x0.22mm² / AWG 24

Rev.date: 2023-10-10

Customs tariff no: 8544429010 Country of origin: Sweden



- PE di-electric insulation for low Capacitance
- High purity tin plated copper wires
- Flexible & robust construction



4BNC-4BNC Cable

Audio/Video Multi Core Co-ax 75 Ohm

AV-4 comprises 4 individual 75 Ohm rated coax cores, surrounded by a common overall foil screen, which further minimises RF break-through. Each core has a braided screen of tin plated OFC. The Supra AV series is of very low capacitance owing to the PE foam insulation. The construction is especially developed for audio & video use, and suits several applications with DB25, Scart, RCA, S-VHS and BNC connectors. The timing error is less than 2.2 ns which enables accurate RGB transmission.

Applications: Game consoles, Home Theatre, Video walls, High resolution video projection, CG workstations or Studio tie lines. RGB/S-video/Composite Video/Component Video.

CONSTRUCTION

Cable: SUPRA AV-4
Jacket: PVC GA78, round

Diameter: 9.5mm Colour: Iceblue

Marking: SUPRA AV-4 > Made in Sweden > Meter mark

Screen connection: Semi-balanced, the outer screen is only connected at the source end

Connectors: Supra BNC-3

- Type: 4 BNC male > 4 BNC male, red, green, blue & yellow

- Material: 24K Gold plated OFC

Colour: Gold
 Locking: Twist-lock
 Solder tin: Almit SR34 Super

Signal direction: Follow the arrows > Source > Receiver

Packing <4m: Blister 25 x 21.5 x 4.8cm Packing >4m: Blister 31.5 x 25.4 x 6cm

Char. impedance: 75 Ohm

Damping: 1MHz/1.4db, 5MHz/3.1dB, 10MHz/4.4dB, 50MHz/9.8dB

Special length are made upon order, add only additional cost per extra meter.

