Shielded Filter Fuse 16A Switch Surge Prot. DC-blocker USB-socket



SUPRA MAINS BLOCK MD-16-EU/SP

Screened Mains block 16A with surge protection & NIF-filter Rev.date: 2023-01-13 Customs tariff no: 8536901000 Country of origin: Sweden



SUPRA Mains Block MD-16-EU/SP

Supra LoRad MD mains blocks are designed to shield and filter noise and protect the electronic gear from surges. The NIF-filter (Non-Intrusive Filtering) is a mild RFI (Radio Frequency Interference) filter damping the high frequency noise from all sorts of modern household sources. It is possible to order with custom configuration and have a capacity to suppress noise floor up to 40 dB! The SP-models are all equipped with the Supra Surge Protection which protects all three ways; i.e. Live to Earth, Neutral to Earth and Live to Neutral. The standard surge protection manufacturer think that it is sufficient to offer only Live to Neutral protection, and they do not protect against field surges by proximate lightning strikes. The only better way to protect your equipment compared to Supra SP is to disconnect all mains power, interconnects and communications with adjacent devices completely

All parts are made in Sweden or Germany & assambled in our factory in Ljungskile, Sweden.

- SP three-way surge protection rejects close perimeter lightning & other surges
- Noise damping up to 40 dB!
- Internal wiring of 2.5 mm2 oxygen-free copper leads
- Support a staggering peak power 3680 Watt @ 230 Volt and 16 Ampere
- Protect both you and your gear from various alternating fields and your gear from Surges
- Wall mounted or standing on a flat hard surface. Rubber feet and brackets included
- Custom tailored NIF-filter from Ben Duncan Research in UK
- Shielded aluminum chassis prevents electric, electro-magnetic and magnetic fields

CONSTRUCTION	Note! 16A Inlet
Chassis:	Aluminum
Standard:	European Standard
Inlet socket:	SUPRA MCH-16, 16A
Outlet sockets:	8 to 15 x SUPRA MCH-16/EU, Schuko
Rated Current/Voltage:	16A / 250V / 3680W
Max RFI Noise damping:	40dB, increased filtering
Surge protection, type 3:	Uc = 2,5kV (Phase to Neutral); 4,0kV (Phase or Neutral to ground)
	Up = 2,0kV (Phase to Neutral); 2,05kV (Phase or Neutral to earth) (Cable not
Width & height (WxH):	90x50mm included!
Length (L):	MD08-EU/SP = 837mm + 52mm for each additional socket
Standard filtering:	No NIF-filter for outlet no 1-2.
	All outlets are surge protected.
	Increased filtering, the last socket got most damping
	red with or without filters for any of the sockets.
Power Amps are recommend	ed to be connected to an unfiltered outlet.

Connect the Mains block with a LoRad cord set (16A) further reduce noise by 6-12 dB!

PRODUCT	Qty	Part no.	EAN-13	E-no	Carton	Weight
MAINS BLOCK MD08-16-EU/SP	1PC	3024000089	7330060202162	2403782	10	1,67
MAINS BLOCK MD10-16-EU/SP	1PC	3024000139	7330060205668		10	2,02
MAINS BLOCK MD15-16-EU/SP	1PC	3024000352	7330060206153			2,41

www.supracables.se