

# SUPRA MB01/H STAROUAD FRHF

Star quad Mic/Line Installation cable Gauge: 1x5x0.24mm2 / AWG 23

Rev.date: 2023-05-25

Customs tariff no: 8544499390 Country of origin: Sweden

- Excellent flame retardancy- Halogen free low smoke
- Star quad configuration, low attenuation
- Low capacitance low microphony
- Low mechanical friction jacket, perfect for installation



## MB01/H Star Quad FRHF - Halogen free & flame retardant

A durable, strong, flame resistant professional Mic/line installation cable

A Slim star quad construction perfect for installation in conduit hoses. Very good electrical and mechanical properties for a long service life. It can be used both as single-end as well as balanced, we recommend balanced operation at longer lengths (> 5 meters). The cable's construction is uncompromisingly designed for microphones and instruments and other line applications. The 4 conductors can be cross-coupled for extremely low attenuation.

#### Halogen Free & Fire Retardant

Supra professional series are fire retandant and halogen-free allowing them to be used professionally in public spaces. As soon as there are large events where the public is present there are tough regulations on all parts when it comes to durability, fire resistance and emissions of toxic fumes in case of a fire. Fire rating Dca-s1, d1, smoke density: s1, particles released: d1

#### CONSTRUCTION

Conductors (x4): Tin plated Cu-wire OFC 5N 19x0.127 mm

4x0,24mm2 / AWG 23 Cross section Area:

PE, Red, blue, white & black. Twisted pair. Insulation:

Alu/Pet foil Screen:

Screen coverage: 100%

Tin plated OFC drain-wire 19x0.127mm Screen connection:

**Jacket:** PE ECCOH 5943 FRHF, round

Jacket thickness. 1.5 mm Diameter. 4.2 mm

Black (other colours upon order) Colour

Marking: SUPRA MB01/H Star Quad > Made in Sweden > Meter mark

Weight: 26 kg/km


Packing: Bobbin 300m och 500m (other lengths upon order)

Suitable plugs: Supra RCA-6, RCA-6SC & Swift XLR

### ELECTRICAL SPECIFCATION

MB01/H STAR QUAD FRHF BLK B500

Resistance: 72 ohm/km Capacitance: 52 pF/m



www.supracables.se

500M 1001800596









7330060207365

