


SUPRA MB02/H 2PRS LINE FRHF

Mic/Line Installation cable - 2 pairs Gauge: 2x3x0.24mm² / AWG 23

Rev.date: 2023-04-20

Customs tariff no: 8544499390 Country of origin: Sweden

- Excellent flame retardancy- Halogen free low smoke
- Low capacitance low microphony
- Separate shields for efficient noise rejection
- Low mechanical friction jacket, perfect for installation



MB02/H FRHF - Halogen Free & Fire Retardant - Mic/Line stereo cable

Supra MB-series - A durable, strong, flame resistant professional installation cable
The conductors of multi-strand tinplated 5N purity copper, together with the PE di-electric (insulation)

The conductors of multi-strand tinplated 5N purity copper, together with the PE di-electric (insulation) provides for a low capacitance professional installation cable with very good electrical properties. The Supra professional series of cables have been recognized as trustworthy partners on-stage and in studios for a long period of time. MB-02/H is a dual channel analogue installation cable aimed for longer analogue transmissions in e.g. studios. Very good electrical and mechanical properties for a long service life. It can be used both as single-end as well as balanced, we recommend balanced operation at longer lengths (> 5 meters).

Halogen Free & Fire Retardant

Supra professional series are fire retandant and halogen-free allowing them to be used professionally in public spaces. As soon as there are large events where the public is present there are tough regulations on all parts when it comes to durability, fire resistance and emissions of toxic fumes in case of a fire.

CONSTRUCTION

Conductors (x4): Tin plated Cu-wire OFC 5N 19x0.127 mm

Cross section Area: 2x0,24mm2 / AWG 23

Insulation: PE, Blue & Red. Twisted pair.

Screen: Alu/Pet foil Screen coverage: 100%

Screen connection: Tin plated OFC drain-wire 19x0.127mm

Parts 2 twisted pairs, PE jacket with coloured yarn for easy identification

Jacket: PE ECCOH 5943 FRHF, round

Jacket wall thickness: 1.5 mm Diameter: 7 mm

Colour Anthracite grey (other colours upon order)

Marking: SUPRA MB02/H > Made in Sweden > Meter mark

Weight: 42 kg/km

Packing: Bobbin 200m (other lengths upon order)
Suitable plugs: Supra RCA-6, RCA-6SC & Swift XLR

ELECTRICAL SPECIFCATION

Resistance: 72 ohm/km Capacitance: 52 pF/m





0402-CPR-7P04047-1

www.supracables.se

EN50399:2011 & EN60332-1-2:2004/A1

:2015/A11:2016

PRODUCT	Qty	Part.no	EAN-13	E-no
MB02-JP/H 2PRS LINE FRHF GREY B200	200M	1001800174	7330060002151	4866403