

# SUPRA MB04/H 4PRS LINE FRHF

Mic/Line Installation cable - 4 pairs Gauge: 4x 3x0.24mm<sup>2</sup> / AWG 23 Rev.date: 2023-05-25 Customs tariff no: 8544499390 Country of origin: Sweden

- Low capacitance low microphony
- Excellent flame retardancy- Halogen free low smoke
- Separate shields for efficient noise rejection
- Low mechanical friction jacket, perfect for installation

## MB04/H FRHF - Halogen Free & Fire Retardant - Mic/Line stereo cable

Supra MB-series - A durable, strong, flame resistant professional installation cable The conductors of multi-strand tinplated 5N purity copper, together with the PE di-electric (insulation) provides for a low capacitance professional installation cable with very good electrical properties. The Supra professional series of cables have been recognized as trustworthy partners on-stage and in studios for a long period of time. MB-04/H is a dual channel analogue installation cable aimed for longer analogue transmissions in e.g. studios. Very good electrical and mechanical properties for a long service life. It can be used both as single-end as well as balanced, we recommend balanced operation at longer lengths (> 5 meters).

#### Halogen Free & Fire Retardant

Supra professional series are fire retandant and halogen-free allowing them to be used professionally in public spaces. As soon as there are large events where the public is present there are tough regulations on all parts when it comes to durability, fire resistance and emissions of toxic fumes in case of a fire.

## CONSTRUCTION

Conductors (x2):	Tin plated Cu-wire OFC 5N 19x0.127 mm	
Cross section Area:	4x 2x0,24mm2 / AWG 23	
Insulation:	PE, Blue & Red. Twisted pair.	FLAME
Screen:	Alu/Pet foil	RETARDANT
Screen coverage:	100%	
Screen connection:	Tin plated OFC drain-wire 19x0.127mm	
Parts	4 twisted pairs, PE jacket with coloured yarn for easy identification	
Jacket:	PE ECCOH 5943 FRHF, round	
Jacket wall thickness:	1.5 mm	Dca-s1,d1
Diameter:	8 mm	0402-CPR-7P04047-1 EN50399:2011 &
Colour	Anthracite grey (other colours upon order)	EN60332-1-2:2004/A1 :2015/A11:2016
Marking:	SUPRA MB04/H > Made in Sweden > Meter mark	www.supracables.se
Weight:	72 kg/km	NNT · COM
Packing:	Bobbin 100m (other lengths upon order)	Columbia and Columbia
Suitable plugs:	Supra RCA-6, RCA-6SC & Swift XLR	ROHS
_		1000

### ELECTRICAL SPECIFCATION

Resistance:72 ohm/kmCapacitance:52 pF/m

 PRODUCT
 Qty
 Part.no
 EAN-13
 E-no

 MB04-JP/H 4PRS LINE FRHF GREY B100
 100M
 1001800182
 7330060002168
 4866413

www.supracables.se