

LORAD 2.5 CS-16-BS MAINS CORD SET

Tin plated & screened Mains Cord Set, 250V/16A Gauge: 3x2.5mm² / AWG 13 Rev.date: 2023-08-14 Customs tariff no: 8544499500 Country of origin: Sweden

- Screened mains flex cable low radiation
- Gold plated Connectors
- Tin plated OFC wires Corrosion restistant
- Protects both from electric & magnetic fields.

LoRad - Low Radiation

Shielded cord set comprising Supra LoRad 3x2.5mm2 cable, Supra SWF-16 female connector (IEC-320) & Supra MC-BS male plug. Cable current rating up to 16 Ampere continuously. British & Irish standard 13 Ampere wall socket. Fits our British LoRad mains power distribution blocks with more than 6 outlets. The cable is intended for Supra LoRad mains block & for connecting hi-fi and multimedia devices 16 Ampere power cords according to the IEC-320 Standard. LoRad means "Low Radiation" & the design of these mains flex cables minimises both electrical & magnetic alternating fields. Allows your hi-fi gear the most welcome benefit of all, the possibility to be electrically silent, when it is supposed to be. Only then, the tiniest details and nuances will become more clearly audible. LoRad protects the surrounding area both from alternating fields radiating from the cable as well as from RF pick-up of surrounding airborne EM noise fields. (* Related cord set LoRad 2.5 SPC CS-BS with SWF-10 female plug is rated 10/13A)

- The short pitch twisting of the conductors cancels the magnetic alternating fields and will not affect adjacent interconnects with external noise.
- LoRad will result in a cleaner sound, a better picture and a more healthy home and working environment with reduced levels of harmful fields. Supra SWF-16
- The screen protects your equipment from radiated mains, RF pick-up from local sources.

CONSTRUCTION

Cable:	Lorad 3x2.5	
Cross section area:	Tin plated OFC 3x2.5mm2 / AWG 13	16A 250V~
Screen:	Semi-conductive Nylon tape, black, coverage 100%, drain wire	LoRad 2.5 CS-16-BS
Jacket:	PVC GA78, round. D=11mm	
Cable colour:	Ice Blue (other colours upon special order)	Supra SWF-10
Marking:	SUPRA LORAD 3G2.5 + Made in Sweden + Meter mark	10A 🖳 🔘
Connectors:	MC-BS male with 13A fuse to SWF-16 16A C19 IEC320 female plug	250V~ S
- Pin Material:	24K Gold plated Copper Alloy	
- Pin connection:	Screw/clamp	NE SWF-105
- Colour:	Ice blue / Anthracite Grey	SUPRA
Cable direction:	MC-BS plug to wall socket & SWF16 to device power inlet	* LoRad 2.5 CS-BS
Rated Voltage/current:	250V / 16A / 13A fuse	
Packing:	1-2m Blister 25x21.5x4.8cm, 4m Blister 31,5x25,4x6,0cm	RoHS

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the British safety regulations & European safety regulation HD21.5 S3. Standard lengths as below, special length cables upon order.

8 1	0	1			
PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 2.5 CS-16-BS 1M	1PC	3004100560	7330060205590	25	0,37
LORAD 2.5 CS-16-BS 1.5M	1PC	3004100578	7330060205606	25	0,48
LORAD 2.5 CS-16-BS 2M	1PC	3004100586	7330060205613	25	0,58
LORAD 2.5 CS-16-BS 4M	1PC	3004100594	7330060205620	13	1,04
			1 1		

COMPLIA

www.supracables.se