3x2.5mm² X Screened X Angled Schuko X 10A C13 plug X

COMPLIAN

REACH



LORAD 2.5 CS-EU/ANGLED MAINS CORD SET

Screened Mains Cord Set, 250V/10A Gauge: 3x2.5mm² / AWG 13 Rev.date: 2022-08-30 Customs tariff no: 8544499500 Country of origin: Sweden

- Screened mains flex cable
- Gold plated Connectors, angled Schuko plug
- Tin plated OFC wires Corrosion restistant
- Protects both from electric & magnetic fields.

LoRad - Low Radiation

Shielded cord set comprising Supra LoRad 3 x 2.5 mm2 cable, Supra SWF10 female connector (IEC-320) and Supra SW-EU/A male plug. Current rating 10 A continuously. EU-version, with angled Schuko plug, is the most common standard throughout Europe. Exceptions are Denmark, Italy, Switzerland, Ireland and Britain. Fits our LoRad mains power distribution blocks rated 10A. LoRad means Low Radiation and the design of these mains flex cables minimises both electric and magnetic alternating fields. Allow your hi-fi gear the most welcome benefit of all, the possibility to be silent, when supposed to. Only then, the tiniest details and notes will become clearly audible. LoRad protects both from alternating fields radiating from the cable as well as from pick-up of surrounding airborne noise fields.

- Short pitch twisting of the lead cores cancels the magnetic alternating fields and will not infect adjacent interconnects with noise feedback.
- LoRad will result in a cleaner sound, better picture and a more healthy home and working invironment with low levels of harmful fields.
- The screen protects your equipment from radiated mains, RF pick-up.

CONSTRUCTION

		E.C.
Cable:	LoRad 3x2.5	
Cross section area:	3x2.5mm2 / AWG 13	
Screen:	Semi-conductive Nylon tape, black, 100%	
Jacket:	PVC GA78, round	
Diameter:	11mm	
Cable colour:	Iceblue (other colours upon order)	
Marking:	SUPRA LORAD 3G1.5 + Made in Sweden + Meter mark	10A 🕀 🔿
Connectors:	SW-EU/Angled Schuko male & SWF-10s 10A C13 IEC320 female	250V~ S
- Pin Material:	24K Gold plated Copper	NE SWF-105
- Pin connection:	Screw/clamp	SUPRA
- Colour:	Anthracite Grey	SUPHA
Cable direction:	Follow the arrows > Wall socket > Power inlet	
Rated Voltage/current:	250V / 10A	
Packing:	1-2m Blister 25x21.5x4.8cm, 4m Blister 31,5x25,4x6,0cm	RoHS 🐕

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. Lorad are tested and certified by Intertek Sweden, meeting the European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.

PRODUCT	Qty	Part.no	EAN-13	Crt	Weight		
LORAD 2.5 CS-EU/ANGLED 1M	1PC	3002100034	7330060205439	25	0,37		
LORAD 2.5 CS-EU/ANGLED 1.5M	1PC	3002100018	7330060205415	25	0,48		
LORAD 2.5 CS-EU/ANGLED 2M	1PC	3002100026	7330060205422	25	0,58		
LORAD 2.5 CS-EU/ANGLED 4M	1PC	3002100042	7330060205446	13	1,04		
1 1							

www.supracables.se