

LORAD 2.5 CS-16-EU/A MAINS CORD SET

Screened Mains Cord Set, 250V/16A

Gauge: 3x2.5mm² / AWG 13

Rev.date: 2022-08-30

Customs tariff no: 8544499500

Country of origin: Sweden

16A

- Screened mains flex cable
- Gold plated Connectors, Angled Schuko plug
- Tin plated OFC wires - Corrosion resistant
- Protects both from electric & magnetic fields.



LoRad - Low Radiation

Shielded cord set comprising Supra LoRad 3 x 2.5 mm² cable, Supra SWF16 female connector (IEC-320) and Supra SW-EU/A male plug. Current rating 16 A continuously. EU-version, with angled Schuko plug, is the most common standard throughout Europe. Exceptions are Denmark, Italy, Switzerland, Ireland and Britain. Fits our LoRad mains power distribution blocks rated 16A. LoRad means Low Radiation and the design of these mains flex cables minimises both electric and magnetic alternating fields. Allow your hi-fi gear the most welcome benefit of all, the possibility to be silent, when supposed to. Only then, the tiniest details and notes will become clearly audible. LoRad protects both from alternating fields radiating from the cable as well as from pick-up of surrounding airborne noise fields.

- Short pitch twisting of the lead cores cancels the magnetic alternating fields and will not infect adjacent interconnects with noise feedback.
- LoRad will result in a cleaner sound, better picture and a more healthy home and working environment with low levels of harmful fields.
- The screen protects your equipment from radiated mains, RF pick-up.

CONSTRUCTION

Cable:	LoRad 3x2.5
Cross section area:	3x2.5mm ² / AWG 13
Screen:	Semi-conductive Nylon tape, black, 100%
Jacket:	PVC GA78, round
Diameter:	11mm
Cable colour:	Iceblue (other colours upon order)
Marking:	SUPRA LORAD 3G2.5 + Made in Sweden + Meter mark
Connectors:	SW-EU/A Schuko male to SWF-16 16A C19 IEC320 female plug
- Pin Material:	24K Gold plated Copper
- Pin connection:	Screw/clamp
- Colour:	Anthracite Grey
Cable direction:	Follow the arrows > Wall socket > Power inlet
Rated Voltage/current:	250V / 16A
Packing:	1-2m Blister 25x21.5x4.8cm, 4m Blister 31,5x25,4x6,0cm



SWF-16 16A C19

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.

PRODUCT	Qty	Part.nr	EAN-13	E-no	Carton Weight
LORAD 2.5 CS-16-EU/ANGLED 1M	1PCS	3002100083	7330060205460	25	0,37
LORAD 2.5 CS-16-EU/ANGLED 1.5M	1PCS	3002100075	7330060205453	25	0,48
LORAD 2.5 CS-16-EU/ANGLED 2M	1PCS	3002100091	7330060205477	25	0,58
LORAD 2.5 CS-16-EU/ANGLED 4M	1PCS	3002100109	7330060205484	13	1,04

