



SUPRA

19.68

Outer layer of 12 insulated #ires, clockwise wound.

Fixing insulati

SUPRA SWORD 2x3.0 COMBICON

High end center loudspeaker cable plated with banana/spade Gauge: 2x3.0mm² / AWG 12 Rev.date: 2022-08-30 Customs tariff no: 8544429010 Country of origin: Sweden

- Transparent and dynamic sound
- Bifilar wound litz conductors
- Interchangeable connectors with M6 thread, banana/spade
- 24K Gold plated OFC connectors

Sword 2x3.0 Combicon - Mono Center Speaker

The base of Supra Sword's superior performance is the bifilar-wound litz conductors comprising 24 individually insulated strands per pole, 12 wound in one direction, the remaining 12 in the opposite, resulting in magnetic field cancellation and very low inductance. Further, the litz wound and individually insulated strands cancels the dynamic skin-effect. The Sword behaves as a non-inductive and in-phase cable through the entire audible frequency spectra. The only thing not cancelled is the sound, allowing you to hear every little note of the music, at full dynamics. Sword will maintain the true signal put out from your Hi-Fi system, giving a completely transparent transition from amplifier to speaker. You will hear the music, nothing more, nothing less.

Sword comes with crimped M6 threaded adaptors and a set of connectors with corresponding threads. The pictures show spades and banana/BFA connectors, as well as the spade replaced with banana/BFA directly screwed onto the body. The connector body and wire are crimped together under at high pressure, making a perfect, air tight, joint.

CONSTRUCTION

			\	anti-clockijse ikoundi	
Cable:	Sword 2x3.0	\backslash			
Conductors (x2)	2x12x0.40 (Enameled)				
Area:	2x3.0mm2 / AWG 12			Core of FE.	
Jacket:	PVC GA78, 8-model				
Diameter:	20x9 mm				
Colour:	Iceblue	Jacket	The 12 wires of the inner layer are connected with the 12 wires of the		
Markning:	SUPRA SWORD 2x3.0 > Made in Sweden >	Meter mark	outer layer, then all together to the plug.		
Configuration:	Mono, 2 > 2 connectors, Right = red, left = b	lack			
Connectors:	Combicon, 4 x Banana M6 pins & 4 x spade	M6 are included	d		
- Material:	24K gold plated OFC Copper				
- Connection:	Crimp, 4 x Combicon CB03 M6				
- Insulation:	Sleeve 2 x S9 red, 2 x S9 black	1		1591-COM	
Signal direction:	Follow the arrows > amplifier > Speaker	(TTP)		ROHS	
Packing:	Carton 31x30x7 cm	ALL AND ALL AN			
-				REACH	

Standard lengths as below, special lengths upon order.

PRODUCT	Qty	Part.no	EAN-13	Weight
SWORD COMBICON 1X2M	1PC	1000100238	7330060200069	0,8
SWORD COMBICON 1X3M	1PC	1000100063	7330060001062	1,0
SWORD COMBICON 1X4M	1PC	1000100246	7330060200076	1,2

www.supracables.se