

LORAD 1.5 CS-BS MAINS CORD SET

Tin plated & screened Mains Cord Set, 250V/13A

Gauge: 3x1.5mm² / AWG 15

Rev.date: 2023-08-11

Customs tariff no: 8544499500

Country of origin: Sweden

- Screened mains flex cable - low radiation
- Gold plated Connectors
- Tin plated OFC wires - Corrosion resistant
- Protects both from electric & magnetic fields.




LoRad - Low Radiation

Shielded cord set comprising Supra LoRad 3x1.5mm² cable, Supra SWF-10 female connector (IEC-320) & Supra MC-BS male plug. Cable current rating up to 16 Ampere continuously. British & Irish standard 13 Ampere wall socket. Fits our British LoRad mains power distribution blocks with up to 6 outlets. The cable is intended for Supra LoRad mains block & for connecting hi-fi and multimedia devices 10/13 Ampere power cords according to the IEC-320 Standard. LoRad means "Low Radiation" & the design of these mains flex cables minimises both electrical & magnetic alternating fields. Allows your hi-fi gear the most welcome benefit of all, the possibility to be electrically silent, when it is supposed to be. Only then, the tiniest details and nuances will become more clearly audible. LoRad protects the surrounding area both from alternating fields radiating from the cable as well as from RF pick-up of surrounding airborne EM noise fields.

- The short pitch twisting of the conductors cancels the magnetic alternating fields and will not affect adjacent interconnects with external noise.
- LoRad will result in a cleaner sound, a better picture and a more healthy home and working environment with reduced levels of harmful fields.
- The screen protects your equipment from radiated mains, RF pick-up from local sources.

CONSTRUCTION

Cable:	Lorad 3x1.5
Cross section area:	Tin plated OFC 3x1.5mm ² / AWG 15
Screen:	Semi-conductive Nylon tape, black, coverage 100%, drain wire
Jacket:	PVC GA78, round. D=9.5mm
Cable colour:	Ice Blue (other colours upon special order)
Marking:	SUPRA LORAD 3G1.5 + Made in Sweden + Meter mark
Connectors:	MC-BS male with 13A fuse to SWF-10s 10A C13 IEC320 female plug
- Pin Material:	24K Gold plated Copper Alloy
- Pin connection:	Screw/clamp
- Colour:	Ice blue / Anthracite Grey
Cable direction:	MC-BS plug to wall socket & SWF10 to device power inlet
Rated Voltage/current:	250V / 13A fuse
Packing:	1-2m Blister 25x21.5x4.8cm, 4m Blister 31,5x25,4x6,0cm



Supra SWF-10

Note! The connector must be connected to a wall socket with a ground terminal for the full LoRad effect to take place. LoRad are tested and certified by Intertek Sweden, meeting the British safety regulations & European safety regulation HD21.5 S3.

Standard lengths as below, special length cables upon order.



PRODUCT	Qty	Part.no	EAN-13	Carton	Weight
LORAD 1.5 CS-BS 1M	1PC	3004100222	7330060009129	25	0,33
LORAD 1.5 CS-BS 1.5M	1PC	3004100123	7330060205552	25	0,38
LORAD 1.5 CS-BS 2M	1PC	3004100172	7330060009136	25	0,43
LORAD 1.5 CS-BS 4M	1PC	3004100230	7330060200014	13	0,74